

DOCTOR OF PHILOSOPHY

ON THE QUASIMONOTONICITY OF A SQUARE LINEAR OPERATOR WITH RESPECT TO A NONNEGATIVE CONE

Philip Beaver-Major, United States Army
B.S., United States Military Academy, 1983
M.S., Naval Postgraduate School, 1991

Doctor of Philosophy in Applied Mathematics-June 1998

Advisor: David Canright, Department of Mathematics

Committee: Christopher L. Frenzen, Department of Mathematics

Robert F. Dell, Department of Operations Research

Clyde L. Scandrett, Department of Mathematics

Maurice D. Weir, Department of Mathematics

The question of when a square, linear operator is quasimonotone nondecreasing with respect to a nonnegative cone was posed for the application of vector Lyapunov functions in 1974. Necessary conditions were given in 1980, which were based on the spectrum and the first eigenvector. This dissertation gives necessary and sufficient conditions for the case of the real spectrum when the first eigenvector is in the nonnegative orthant, and when the first eigenvector is in the boundary of the nonnegative orthant, it gives conditions based on the reducibility of the matrix. For the complex spectrum, in the presence of a positive first eigenvector the problem is shown to be equivalent to the irreducible nonnegative inverse eigenvalue problem.

DoD KEY TECHNOLOGY AREA: Other (Applied Mathematics)

KEYWORDS: Quasimonotonicity, Nonnegative Cone

LOW LATITUDE IONOSPHERIC EFFECTS ON RADIOWAVE PROPAGATION

Rasler W. Smith, DoD Civilian

B.S.E.E., University of Texas at Austin, 1979

M.S.E.E., Naval Postgraduate School, 1990

E.E., Naval Postgraduate School, 1990

Doctor of Philosophy in Electrical Engineering-June 1998

Advisor: Richard W. Adler, Department of Electrical and Computer Engineering

PhD Committee: Gus K. Lott, Department of Electrical and Computer Engineering

Jeffrey B. Knorr, Department of Electrical and Computer Engineering

Wilbur R. Vincent, Department of Electrical and Computer Engineering

David D. Cleary, Department of Physics

Kenneth L. Davidson, Department of Meteorology

This dissertation provides experimental observations and analyses that associate low-latitude transionospheric signal scintillation with transequatorial VHF radio propagation and errors in transionospheric geopositioning.

The experiment observed equatorial-region ionospheric total electron content (TEC) derived from Global Positioning System (GPS) signals using receivers on Oahu, Hawaii, Christmas Island, and Rarotonga, Cook Islands. The experiment simultaneously measured VHF transequatorial propagation of VHF television signals from Hawaii to Rarotonga.

DOCTOR OF PHILOSOPHY

Analysis shows that a moving second moment of vertical-equivalent TEC strongly correlates to each VHF transequatorial radio propagation event. From experimental observation analysis, the author develops models for prediction of TEP and time-space distribution of low-latitude transionospheric scintillation.

The author also develops equations that show the potential errors in time, frequency, and angle used in geopositioning solutions. These three parameters are potentially correctable using these techniques.

DoD KEY TECHNOLOGY AREA: Sensors

KEYWORDS: Low-Latitude, Ionosphere, Equatorial, Scintillation, Geopositioning, Global Positioning System, GPS, Total Electron Content, TEC, Transequatorial Propagation, TEP

CHANNEL ALLOCATION IN WIRELESS INTEGRATED SERVICES NETWORKS FOR LOW-BIT-RATE APPLICATIONS

Amir Uziel-Major, Israeli Army

B.Sc., Tel-Aviv University, 1988

Doctor of Philosophy in Electrical Engineering-June 1998

Advisor: Murali Tummala, Department of Electrical and Computer Engineering

PhD Committee: Gus K. Lott, Jr., Department of Electrical and Computer Engineering

Craig W. Rasmussen, Department of Mathematics

Gilbert M. Lundy, Department of Computer Science

This work addresses issues related to the design and performance of a wireless integrated services network with emphasis on a tactical framework. We propose an asynchronous transfer mode (ATM)-like protocol architecture for the mobile network, which is an extension of schemes proposed in the literature. A medium-access-control (MAC) scheme, based on slot reservation by the remotes, is proposed for the network. Traffic models for low-bit-rate applications, suitable for low-capacity channels, such as a multiple-access (macrocell) wireless network, are presented. New bi-directional speech-conversation and bursty data models are proposed.

The issue of scheduling in wireline integrated services networks is thoroughly addressed and new algorithms are proposed. An analytical scheme to obtain the required (static) capacity for homogeneous sources based on their Markov-chain characterization is provided. A necessary condition for optimality of a scheduling algorithm is the balance of cell-loss-probability (CLP) ratios to values approaching 1 from below, on the boundary of the admissible region. The balanced-CLP-ratio (BCLPR) algorithm satisfies this condition but ignores the deadlines of the cells. The shortest time to extinction (STE) with BCLPR (STEBR) algorithm, proposed here for the first time, utilizes the earliest-deadline-first concept while satisfying the necessary condition. A proof is provided to show that the STEBR decisions are optimal at each service slot given that no information about future traffic arrivals is available. Simulation results indicate that STEBR admits more sources and yields larger normalized channel throughput (by up to 4%) than STE.

The wireless network presents a case of distributed queues at the command post (CP) and in the remotes, making channel allocation more involved compared to scheduling in wireline systems. Based on the schedulers discussed for the wireline queue, corresponding algorithms for operation in the wireless network are developed. The cases of partial and complete status reports of the remotes are investigated as a function of the network load in five representative scenarios. The following (descending) order of performance under both partial and complete status reports is maintained in all scenarios: STEBR, STE, BCLPR, and static allocation. Performance of the schedulers using partial or complete status reports depends on the value of the normalized throughput. The complete-status mechanism is preferred whenever the normalized throughput is smaller than 0.70-0.75; partial status reports are sufficient for normalized throughput larger than 0.70-0.75. A hybrid approach that makes use of this outcome is proposed to best utilize the available channel capacity under all possible levels of network load.

DoD KEY TECHNOLOGY AREA: Command, Control, and Communications, Modeling and Simulation, Other (Networking)

KEYWORDS: B-ISDN, ATM, MAC, Scheduling, Channel Allocation, Mobile Networks, Low-Bit-Rate Source Models
